



# NOTES

1. PHOSPHATE PER MIL-DTL-16232 TYPE Z, CLASS 2 w/BAKE
2. HEAT TREAT: QUENCH & TEMPER 82.5-84.5 HR15N
3. DIMENSIONS APPLY BEFORE PLATING

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR: MACH  $\pm 1/2$  Deg  
TWO PLACE DECIMAL  $\pm .01$   
THREE PLACE DECIMAL  $\pm .005$

MATERIAL  
SPRING STEEL

FINISH  
SEE NOTE 1

DRAWING IS NOT TO SCALE

	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		

SEASTROM MFG

BELLEVILLE  
SPRING WASHER

SIZE <b>A</b>	DWG. NO. <b>5808-75-32-PH</b>	REV. <b>-</b>
------------------	----------------------------------	------------------

SHEET 1 OF 1