## REFERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 MAX Ø.209 Ø.114 Ø.120

## NOTES

1. BLACK OXIDE PER MIL-DTL-13924 CLASS 1, LIGHT OIL, NO TEST REQUIRED; w/BAKE

2. SCREW SIZE: 4

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING, ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

DIMENSIONS ARE IN INCHES				
TOLERANCES:	D			
FRACTIONAL±1/32				
ANGULAR: MACH±1/2 Deg				
TWO PLACE DECIMAL ±.01	13			
THREE PLACE DECIMAL ±.005	М			
MATERIAL	Q			
HIGH CARBON SPRING STEEL	С			
FINISH				
SEE NOTE 1				

DRAWING IS NOT TO SCALE

	NAME	DATE		SEASTROM N	<b>1</b> EC	
RAWN				3LA3TKOM N	MG	
CHECKED						
NG APPR.				SDDINIC LOCKW	V CTED	
AFG APPR.				SPRING LOCKWASHER		
A.Ç						
COMMENTS:						
				I		
				DWG. NO.		REV.
			Α	5850-11-BO		-
					SHEET 1 C	)F 1

MIN .040-