


| D+/-0.015 | L+/-0.01 | T (Stk)+/-0.001 | H (Max) | W (Base Max) | X+/-0.02 | E+/-0.003 | A+/-0.005 | B+/-0.005 | C+/-0.005 | M+/-0.03 | N+/-0.03 | S (Ref) |
|-----------|----------|-----------------|---------|--------------|----------|-----------|-----------|-----------|-----------|----------|----------|---------|
| 0.260     | 0.312    | 0.012           | 0.360   | 0.300        | 0.200    | 0.071     | 0.156     | 0         | 0         | 0.140    | 0        | 0.032   |



ALL DIMENSIONS ARE TO BE MEASURED WITH THE SPRING CLIP SECURED TO A FLAT SURFACE AND A COMPONENT OF THE NOMINAL DIAMETER IN PLACE.



SEASTROM MANUFACTURING CO., INC.  
 456 SEASTROM STREET  
 TWIN FALLS, IDAHO 83301  
 (208) 737-4300 FAX (208) 734-7222

ALL INFORMATION  
 COPYRIGHTED BY  
 SEASTROM MFG. ©

|                    |   |
|--------------------|---|
| <b>PART NO.:</b>   | 4528-26-31-1  |
| <b>PART NAME:</b>  | Spring Clips 02   |
| <b>MATERIAL:</b>   | Beryllium Copper  |
| <b>HEAT TREAT:</b> | Please refer to Material & Finish Specifications in Engineering Resources |
| <b>FINISH:</b>     | None  |

Dimensions in Inches